

INTERNATIONAL AS FURTHER MATHEMATICS FM02

(9665/FM02) Unit FPSM1 Pure Mathematics, Statistics and Mechanics

Mark scheme

June 2025

Version: 1.0 Final



Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from www.oxfordaqa.com

Copyright information

OxfordAQA retains the copyright on all its publications. However, registered schools/colleges for OxfordAQA are permitted to copy material from this booklet for their own internal use, with the following important exception: OxfordAQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Copyright © 2025 OxfordAQA International Examinations and its licensors. All rights reserved.

Key to mark scheme abbreviations

M	Mark is for method
m	Mark is dependent on one or more M marks and is for method
A	Mark is dependent on M or m marks and is for accuracy
B	Mark is independent of M or m marks and is for method and accuracy
E	Mark is for explanation
✓ or ft	Follow through from previous incorrect result
CAO	Correct answer only
CSO	Correct solution only
AWFW	Anything which falls within
AWRT	Anything which rounds to
ACF	Any correct form
AG	Answer given
SC	Special case
oe	Or equivalent
A2, 1	2 or 1 (or 0) accuracy marks
–x EE	Deduct x marks for each error
NMS	No method shown
PI	Possibly implied
SCA	Substantially correct approach
sf	Significant figure(s)
dp	Decimal place(s)
ISW	Ignore subsequent working

Q	Answer	Marks	Comments
1(a)	$1.2 \times 1.8 - (0.4 - p) \times (0.4 + p)$	M1	Correct expression for determinant
	$2 + p^2$	A1	CAO
		2	

Q	Answer	Marks	Comments
1(b)(i)	Shear parallel to y-axis	B1	Allow vertical shear, shear in direction of y-axis, shear with y-axis invariant, shear in/on/with y-axis oe Ignore any additional descriptions
		1	

Q	Answer	Marks	Comments
1(b)(ii)	$\begin{bmatrix} 1 & 0 \\ k & 1 \end{bmatrix} \begin{bmatrix} 3 \\ 2 \end{bmatrix} = \begin{bmatrix} 3 \\ -4 \end{bmatrix}$	M1	Uses correct matrix equation to obtain an equation in terms of k
	$\Rightarrow 3k + 2 = -4$		
	$k = -2$	A1	CAO
		2	

Q	Answer	Marks	Comments
1(c)	$\mathbf{C} = \begin{bmatrix} 1.2 & 0.4 - p \\ 0.4 + p & 1.8 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ -2 & 1 \end{bmatrix}$	M1	$\mathbf{A} \times \mathbf{B}$ with $\mathbf{B}$ in terms of k or using their k
	$= \begin{bmatrix} 0.4 + 2p & 0.4 - p \\ p - 3.2 & 1.8 \end{bmatrix}$	m1	obtains a 2×2 matrix with at least 2 correct terms ft B in terms of k or using their k Terms may be unsimplified
		A1	CAO
		3	

	Question 1 Total	8	
--	------------------	---	--

Q	Answer	Marks	Comments
2	$hf(2, 5) = 0.05 \times \frac{1}{2^2 - \sqrt{5}}$ $= 0.02834576\dots$ $y_2 = 5 + 0.02834576\dots = 5.02834576\dots$ $y_3 = 5.02834576 + 0.05 \times \frac{1}{2^{2.05} - \sqrt{5.02834576}}$ $[= 5.05468009]$ 5.055	<p>M1</p> <p>A1</p> <p>M1</p> <p>M1</p> <p>A1</p>	<p>Correct substitution into RHS of this expression PI</p> <p>AWRT 0.028 PI</p> <p>5 + their value of $hf(2, 5)$ PI</p> <p>Correct substitution using $x_2 = 2.05$ and their y_2 into second term PI by sight of AWRT 5.054 or 5.055</p> <p>CAO</p>

	Question 2 Total	5	
--	------------------	---	--

Q	Answer	Marks	Comments
3(a)	$\frac{y}{x} = Ax + B$	M1	Divides through by x
	which is a linear relationship [between x and $\frac{y}{x}$]	A1	Obtains correct relationship and gives conclusion
		2	

Q	Answer	Marks	Comments
3(b)(i)		B1	Straight line of best-fit drawn following general trend of points Number of points above the line must be no more than 1 more than number of points below the line and vice versa
		1	

Q	Answer	Marks	Comments
3(b)(ii)	gradient = -0.47 y-intercept = 2.46	B1	Gradient or intercept seen for their straight line of best fit Half a square tolerance for identified points
	$A = -0.47$ $B = 2.46$	B1	AWFW $[-0.5, -0.44]$ for A AWFW $[2.38, 2.55]$ for B Note an award of B0 B1 is possible
		2	

Q	Answer	Marks	Comments
3(c)	$1 = -0.47x^2 + 2.46x$	M1	Correct substitution of their values and $y=1$ into original relationship
	$x = 4.7898$ or $x = 0.4442$	m1	PI Solves resulting quadratic
	$x = 4.8$ or $x = 0.44$	A1ft	ft their A and B Answers must be given to two significant figures and not rejected
		3	
	Question 3 Total	8	

Q	Answer	Marks	Comments
4(a)(i)	$x_1 = \frac{3 \times -3 - 2 \times 3}{-3 - 3} = 2.5$ <p>Linear interpolation also gives the mid point</p>	<p>M1</p> <p>A1</p>	<p>Applies linear interpolation once, must see the calculation of x_1 or equation of line $y = 6x - 15$ or evaluates both $f(2) = -3$ and $f(3) = 3$ which must be seen in part (a)(i)</p> <p>Correct conclusion oe</p> <p>eg $f(2) = f(3)$ so linear interpolation divides the interval in two [as does interval bisection]</p>
		2	

Q	Answer	Marks	Comments
4(a)(ii)	$f\left(\frac{5}{2}\right) = -2.75 \text{ and } f(3) = 3$ <p>Change of sign, so $\frac{5}{2} < \alpha < 3$</p>	<p>M1</p> <p>A1</p>	<p>Correct evaluation of $f\left(\frac{5}{2}\right)$ and $f(3)$</p> <p>One or both may be seen in part (a)(i)</p> <p>Correct conclusion</p> <p>Must state or show that there is a change of sign and concludes that α is present in the interval</p> <p>Reference to $f\left(\frac{5}{2}\right)$ and $f(3)$ must be seen but not necessarily evaluated in part (a)(ii)</p>
		2	

Q	Answer	Marks	Comments
4(b)	$\frac{x_1 - \frac{5}{2}}{3 - x_1} = \frac{2.75}{3}$ $3\left(x_1 - \frac{5}{2}\right) = 2.75(3 - x_1)$ $3x_1 - \frac{15}{2} = \frac{33}{4} - 2.75x_1$ $5.75x_1 = \frac{63}{4}$ $x_1 = \frac{63}{23}$ $[f(x_1)] = -0.778$ $f(x_1) < 0 \text{ so } \frac{63}{23} < \alpha < 3$	<p>M1</p> <p>m1</p> <p>A1</p> <p>B1</p> <p>A1</p>	<p>Obtains correct equation in terms of x_1 or obtains equation of linear interpolation line $y = \frac{23}{2}x - \frac{63}{2}$ or obtains $\frac{p}{0.5 - p} = \frac{2.75}{3}$ oe</p> <p>Condone use of $f\left(\frac{5}{2}\right)$ and $f(3)$ instead of values ft their values from (a)</p> <p>Obtains correct linear equation in terms of x_1 oe</p> <p>Correct calculation of x_1 scores M1 m1, eg $x_1 = \frac{5}{2} + \frac{1}{2} \times \frac{2.75}{2.75 + 3}$, $x_1 = \frac{2.5 \times 3 - 3 \times -2.75}{3 + 2.75}$, $x_1 = \frac{5}{2} + \frac{11}{46}$</p> <p>Condone use of $f\left(\frac{5}{2}\right)$ and $f(3)$ instead of values ft their values from (a)</p> <p>AG Must be convincingly shown $f\left(\frac{5}{2}\right)$ and $f(3)$ must be evaluated</p> <p>Correct linear equation in terms of x_1 or correct calculation of x_1 must be seen</p> <p>AWRT -0.8 Allow truncated -0.7</p> <p>AG Must be convincingly shown Note an award of M1 m1 A0 B1 A1 is possible</p>
		5	
	Question 4 Total	9	

Q	Answer	Marks	Comments
5(a)	$\mathbf{M}^2 = \frac{1}{25} \begin{bmatrix} 2k-3 & 4-k \\ 4k+4 & 3-2k \end{bmatrix} \begin{bmatrix} 2k-3 & 4-k \\ 4k+4 & 3-2k \end{bmatrix}$ $= \frac{1}{25} \begin{bmatrix} (2k-3)^2 + (4-k)(4k+4) & (2k-3)(3-2k) + (4-k)(4k+4) \\ (4k+4)(2k-3) + (3-2k)(4k+4) & (4k+4)(3-2k) + (3-2k)(4k+4) \end{bmatrix}$ $= \frac{1}{25} \begin{bmatrix} 25 & 0 \\ 0 & 25 \end{bmatrix}$ $= \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$	<p>M1</p> <p>M1</p> <p>A1</p>	<p>For $\frac{1}{25} \times$ a 2×2 matrix oe with at least one correct algebraic entry</p> <p>PI</p> <p>For one correctly evaluated entry</p> <p>CAO</p>
		3	

Q	Answer	Marks	Comments
5(b)	$\frac{1}{5} \begin{bmatrix} 2k-3 & 4-k \\ 4k+4 & 3-2k \end{bmatrix} \begin{bmatrix} x \\ 2x \end{bmatrix}$ $= \frac{1}{5} \begin{bmatrix} (2k-3)x + (4-k) \times 2x \\ (4k+4)x + (3-2k) \times 2x \end{bmatrix}$ $= \frac{1}{5} \begin{bmatrix} 5x \\ 10x \end{bmatrix}$ $= \begin{bmatrix} x \\ 2x \end{bmatrix}$ <p>So $y = 2x$ is a line of invariant points</p>	<p>M1</p> <p>A1</p> <p>A1</p>	<p>Applies M correctly to a general point on the line $y = 2x$</p> <p>Obtains $\begin{bmatrix} x \\ 2x \end{bmatrix}$ with an intermediate line and no errors seen</p> <p>Correct conclusion</p>
		3	

Q	Answer	Marks	Comments
5(c)(i)	$k = 0$ gives $\mathbf{M} = \frac{1}{5} \begin{bmatrix} -3 & 4 \\ 4 & 3 \end{bmatrix}$ Reflection [with mirror line] $y = 2x$	M1 A1 A1	Substitutes $k = 0$ Condone $y = (\tan \theta)x$ where $\theta = \mathbf{AWRT} \ 63.4^\circ$ or 1.11 radians or $\tan \theta = \mathbf{AWRT} \ 2.0$
		3	

Q	Answer	Marks	Comments
5(c)(ii)	$a = -\frac{1}{2}$	B1	
		1	

	Question 5 Total	10	
--	-------------------------	-----------	--

Q	Answer	Marks	Comments
6(a)	[Discrete] uniform [distribution]	B1	Must see uniform
		1	

Q	Answer	Marks	Comments
6(b)	$\frac{5}{11}$	B1	oe
		1	

Q	Answer	Marks	Comments
6(c)	$E(X) = \frac{n+1}{2}$ $E(X) = \frac{11+1}{2} = 6$ $Var(X) = \frac{n^2-1}{12}$ $Var(X) = \frac{11^2-1}{12} = 10$ $6a + b = 13$ $10a^2 = 90$ $a = 3$ $b = -5$	<p>B1</p> <p>B1</p> <p>M1</p> <p>A1</p> <p>A1</p>	<p>Obtains $E(X) = \frac{11+1}{2}$ oe PI</p> <p>Obtains $Var(X) = \frac{11^2-1}{12}$ oe PI</p> <p>One correct equation for their mean and variance</p> <p>CAO</p> <p>CAO</p>
		5	

	Question 6 Total	7	
--	------------------	---	--

Q	Answer	Marks	Comments
7(a)	$1 - 0.318 - 0.512 = 0.17$	B1	AG Must be convincingly shown
		1	

Q	Answer	Marks	Comments
7(b)	$G'_Y(t) = 0.512 + 0.17bt^{b-1}$ $1.872 = 0.512 + 0.17b$ $b = 8$	M1 M1 A1	Differentiates $G_Y(t)$ correctly May be in terms of a Condone $G'_Y(1) = 0.512 + 0.17b \times 1^{b-1}$ oe Forms correct equation to find b oe PI Must see $G'_Y(t) = 0.512 + 0.17bt^{b-1}$ oe
		3	

Q	Answer	Marks	Comments
7(c)	$G''_Y(t) = 9.52t^6$ $\text{Var}(Y) = 9.52 + 1.872 - 1.872^2$ $\text{Var}(Y) = 7.887616$	M1 m1 A1ft	Differentiates their $G'_Y(t)$ correctly May be in terms of a and b oe Applies correct variance formula with their $G'_Y(1)$ and $G''_Y(1)$ AWRT 7.89 ft their $0.17b(b - 1) - 1.632384$
		3	

	Question 7 Total	7	
--	-------------------------	----------	--

Q	Answer	Marks	Comments
8(b)	$\frac{0.784 \times 0.88}{0.784 \times 0.88 + 0.216 \times 0.19}$ $= 0.944$	<p>M1</p> <p>Correct calculation for the numerator PI by sight of 0.68992 ft their 0.784</p> <p>M1</p> <p>Correct calculation for the denominator PI by sight of 0.73096 ft their 0.784 and 0.216 provided that they sum to 1</p> <p>A1</p> <p>AWRT 0.944 or $\frac{8624}{9137}$ oe</p>	
		3	
	Question 8 Total	6	

Q	Answer	Marks	Comments
9(a)	MLT^{-2}	B1	Correct dimensions
		1	

Q	Answer	Marks	Comments
9(b)	MLT^{-1}	B1	Correct dimensions
		1	

Q	Answer	Marks	Comments
9(c)	$[\text{Rate of change of momentum}] = \frac{MLT^{-1}}{T}$ $= MLT^{-2}$ $= [\text{Force}]$ <p>So statement is dimensionally consistent</p>	<p>M1</p> <p>A1</p>	<p>Correct dimensions of rate of change of momentum ft their dimensions of momentum Condone use of units for this mark only</p> <p>Concludes argument with $\frac{MLT^{-1}}{T}$ or $\frac{ML}{T \times T}$ or $MLT^{-1}T^{-1}$ seen CSO</p>
		2	

	Question 9 Total	4	
--	------------------	---	--

Q	Answer	Marks	Comments
10(a)	$3 \times 5 + 7 \times (-2) = 3v_A + 7v_B$	M1	Uses $\pm 3 \times 5 \pm 7 \times 2 = \pm 3v_A \pm 7v_B$
	$1 = 3v_A + 7v_B$	A1	Correct equation
	$v_A - v_B = -0.1(5 - (-2))$	M1	Uses $\pm v_A \pm v_B = \pm 0.1(5 \pm 2)$
	$v_A - v_B = -0.7$	A1	Correct equation
	$v_A = -0.39$	A1	Correct speed If units are seen they must be correct
	Speed of A = $0.39 \text{ [m s}^{-1}\text{]}$		
		5	

Q	Answer	Marks	Comments
10(b)	$I = 3 \times (-0.39) - 3 \times 5$	M1	Uses $3 \times (\pm \text{their } v_A \pm 5)$ oe
	$= -16.17$		
	Magnitude = 16.2 [Ns]	A1	Correct magnitude given to 3 s.f. If units are seen they must be correct
		2	

Q	Answer	Marks	Comments
10(c)	$16.17 = F \times 0.05$	M1	Uses $I = Ft$
	$F = 323 \text{ [N]}$	A1	Correct value given to 3 s.f. Allow 324 [N]
		2	

	Question 10 Total	9	
--	-------------------	---	--

Q	Answer	Marks	Comments
11(a)	$\mathbf{v}_{QP} = \begin{bmatrix} V \sin \theta - 3 \cos 10^\circ \\ V \cos \theta + 3 \sin 10^\circ \end{bmatrix}$	<p>M1</p> <p>A1</p>	<p>Finds relative velocity, with at least one correct component of $\mathbf{v}_{PQ}$ or $\mathbf{v}_{QP}$ or obtains $\begin{bmatrix} V \cos \theta + 3 \sin 10^\circ \\ V \sin \theta - 3 \cos 10^\circ \end{bmatrix}$</p> <p>oe Condone as part of an equation to find the magnitude of relative velocity</p> <p>Correct relative velocity oe eg $\begin{bmatrix} V \sin \theta - 3 \sin 100^\circ \\ V \cos \theta - 3 \cos 100^\circ \end{bmatrix}$</p> <p>AWRT 2.95 for $3 \cos 10^\circ$ AWRT 0.52 for $3 \sin 10^\circ$</p>
		2	

Q	Answer	Marks	Comments
11(b)	$360(V \sin \theta - 3 \cos 10^\circ) = 0$ $360(V \cos \theta + 3 \sin 10^\circ) = 1200$ $V \sin \theta = 3 \cos 10^\circ$ $V \cos \theta = \frac{1200}{360} - 3 \sin 10^\circ$ $V = \sqrt{(3 \cos 10^\circ)^2 + \left(\frac{1200}{360} - 3 \sin 10^\circ\right)^2} = 4.1$ $\tan \theta = \frac{3 \cos 10^\circ}{\frac{1200}{360} - 3 \sin 10^\circ}$ $\theta = 46$	<p>M1</p> <p>A1</p> <p>m1 A1</p> <p>A1</p>	<p>Obtains one correct expression in terms of $V \sin \theta$ or $V \cos \theta$ for their $\mathbf{v}_{QP}$ in the form $\begin{bmatrix} \pm V \sin \theta \pm A \\ \pm V \cos \theta \pm B \end{bmatrix}$ or $\begin{bmatrix} \pm V \cos \theta \pm B \\ \pm V \sin \theta \pm A \end{bmatrix}$</p> <p>Obtains correct expressions for $V \sin \theta$ and $V \cos \theta$ oe</p> <p>AWRT 2.95 for $3 \cos 10^\circ$</p> <p>AWRT 2.81 for $\frac{1200}{360} - 3 \sin 10^\circ$</p> <p>PI</p> <p>m1: Eliminates θ or V</p> <p>A1: Correct $V =$ AWRT 4.1</p> <p>Correct $\theta =$ AWRT 46</p>
		5	

Q	Answer	Marks	Comments
11(b) ALT 1	$1200^2 + (6 \times 60 \times 3)^2 - 2 \times 1200 \times 6 \times 60 \times 3 \cos(180 - 100)$ Distance P travels = 1468[.435877] $\frac{\sin \theta}{6 \times 60 \times 3} = \frac{\sin(180 - 100)}{1468.435877}$ $\theta = 46$ $V = 4.1$	M1 A1 m1 A1 A1	Applies cosine rule correctly to obtain a calculation for (distance P travels) ² Obtains distance P travels AWRT 1468 PI Applies sine rule correctly or divides distance P travels by 360 Correct $\theta =$ AWRT 46 Correct $V =$ AWRT 4.1
		5	

Q	Answer	Marks	Comments
11(b) ALT 2	$V^2 = 3^2 + \left(\frac{1200}{6 \times 60}\right)^2 - 2 \times 3 \times \left(\frac{1200}{6 \times 60}\right) \cos(180 - 100)$ $V^2 = 16.6[3814756]$ $V = 4.1$ $\frac{\sin \theta}{3} = \frac{\sin(180 - 100)}{\sqrt{16.63814756}}$ $\theta = 46$	M1 A1 A1 m1 A1	Applies cosine rule correctly to obtain a calculation for V^2 Obtains correct V^2 AWRT 16.6 PI by correct V Correct $V =$ AWRT 4.1 Applies sine rule correctly Correct $\theta =$ AWRT 46
		5	

	Question 11 Total	7	
--	--------------------------	----------	--