

INTERNATIONAL A-LEVEL FURTHER MATHEMATICS FM05

(9665/FM05) Unit FM2 Mechanics

Mark scheme

January 2026

Version: 1.0 Final

Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from www.oxfordaqa.com

Copyright information

OxfordAQA retains the copyright on all its publications. However, registered schools/colleges for OxfordAQA are permitted to copy material from this booklet for their own internal use, with the following important exception: OxfordAQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Copyright © 2026 OxfordAQA International Examinations and its licensors. All rights reserved.

Key to mark scheme abbreviations

M	Mark is for method
m	Mark is dependent on one or more M marks and is for method
A	Mark is dependent on M or m marks and is for accuracy
B	Mark is independent of M or m marks and is for method and accuracy
E	Mark is for explanation
✓ or ft	Follow through from previous incorrect result
CAO	Correct answer only
CSO	Correct solution only
AWFW	Anything which falls within
AWRT	Anything which rounds to
ACF	Any correct form
AG	Answer given
SC	Special case
oe	Or equivalent
A2, 1	2 or 1 (or 0) accuracy marks
–x EE	Deduct x marks for each error
NMS	No method shown
PI	Possibly implied
SCA	Substantially correct approach
sf	Significant figure(s)
dp	Decimal place(s)
ISW	Ignore subsequent working

[illegible]

Q	Answer	Marks	Comments
2(a)	$\text{Work Done} = \int_0^5 \frac{x(5-x)}{4} dx$	M1 A1	M1 Sets up an integral to find the work done A1 Correct integral with correct limits
	$\text{Work Done} = \left[\frac{5x^2}{8} - \frac{x^3}{12} \right]_0^5$ $= \frac{125}{24} \text{ [J]}$	A1	Correct value oe eg $5\frac{5}{24}$
		3	

Q	Answer	Marks	Comments
2(b)	$\frac{125}{24} = \frac{3}{2}v^2 - \frac{3}{2} \times 4^2$	M1	Uses change in KE equals work done ft their work done from part (a). Condone sign errors PI by expression for v with no more than one error eg $6v^2 = \frac{5}{3}x^2 - \frac{1}{3}x^3 + 96$
	$v^2 = \frac{701}{36}$ $v = \frac{\sqrt{701}}{6} \text{ [m s}^{-1}\text{]}$	A1	Correct speed
		2	

	Question 2 Total	5	
--	-------------------------	----------	--


Q	Answer	Marks	Comments
3(a)	$T_1 = 5g$	M1	Equation for the extension of one string
	$5g = \frac{\lambda}{a} e_1$	A1	One correct extension
	$e_1 = \frac{5ag}{\lambda}$	A1	Second correct extension
	$T_2 = 3g$	A1	Correct length OB oe
	$3g = \frac{\lambda}{a} e_2$		
	$e_2 = \frac{3ag}{\lambda}$		
	$OB = 2a + \frac{5ag}{\lambda} + \frac{3ag}{\lambda} = 2a \left(1 + \frac{4g}{\lambda} \right)$	A1	
		4	

Q	Answer	Marks	Comments
3(b)(i)	$2a = 2g + T_2$ $= 2g + 3g$	M1	Applies Newton's Second Law to A Must use a mass of 2 kg. Allow $2a =$ any integer multiple of g
	$a = \frac{5g}{2}$	A1	Correct acceleration
		2	

Q	Answer	Marks	Comments
3(b)(ii)	$3a = 3g - T_2$ $= 3g - 3g$	B1	Correct acceleration
	$a = 0$		
		1	

	Question 3 Total	7	
--	-------------------------	----------	--

Q	Answer	Marks	Comments
4(a)	$\frac{dv}{dt} = g - \frac{v}{4m}$ $\int \frac{1}{g - \frac{v}{4m}} dv = \int 1 dt$ $-4m \ln \left(g - \frac{v}{4m} \right) = t + c$ $t = 0, v = 0 \Rightarrow c = -4m \ln g$ $-4m \ln \left(g - \frac{v}{4m} \right) = t - 4m \ln g$ $\frac{g - \frac{v}{4m}}{g} = e^{-\frac{t}{4m}}$ $v = 4mg \left(1 - e^{-\frac{t}{4m}} \right)$	<p>M1</p> <p>M1</p> <p>A1</p> <p>A1</p> <p>A1</p>	<p>Differential equation</p> <p>Separation of variables</p> <p>Correct integration Condone missing constant of integration</p> <p>Correct constant of integration</p> <p>Correct expression</p>
		5	

Q	Answer	Marks	Comments
4(b)		<p>B1</p> <p>B1</p>	<p>Correct shape</p> <p>Correct asymptote including correct label on the vertical axis</p>
		2	

Q	Answer	Marks	Comments
4(c)	$2mg = 4mg \left(1 - e^{-\frac{t}{4m}} \right)$ $\frac{1}{2} = 1 - e^{-\frac{t}{4m}}$ $-\frac{t}{4m} = \ln \frac{1}{2}$ $t = m \ln 16$	<p>M1</p> <p>A1</p>	<p>Forms equation and solves for t ft their expression for v</p> <p>Correct result using the correct expression for v</p>
		2	
	Question 4 Total	9	

Q	Answer	Marks	Comments
5(a)	$EPE = \frac{1}{2} \times \frac{125}{1.5} \times 0.6^2$	M1	Uses EPE formula
	$EPE = 15 \text{ [J]}$	A1	Correct EPE
		2	

Q	Answer	Marks	Comments
5(b)	Let d be the distance that the particle moves $0.6 \leq d \leq 2.1$	B1	Correct range of values for d PI by use of 0.6 and 2.1
	$15 = 4.2g\mu \times d$	M1 A1	M1: Two term energy equation A1: Correct equation PI by 0.174 or 0.607
	$\mu = \frac{15}{4.2gd}$	M1	Uses range of values for d to find a range of values for μ Must not contain 0 or 1
	$\frac{15}{4.2g \times 2.1} \leq \mu \leq \frac{15}{4.2g \times 0.6}$		
	$0.174 \leq \mu \leq 0.607$	A1	Correct range of values Allow strict inequality signs.
		5	

Q	Answer	Marks	Comments
5(c)	$15 = 4.2g \times \frac{15}{4.2g \times 2.1} \times 0.6 + \frac{1}{2} \times 4.2v^2$	M1 A1ft	M1: Three term energy equation A1ft: Correct equation for their smallest coefficient of friction
	$v^2 = \frac{250}{49} = 5.0966\dots$ $v = \frac{5\sqrt{10}}{7} = 2.258\dots$ $v = 2.3 \text{ [m s}^{-1} \text{ to 2 sf]}$	A1	Correct speed $\frac{5\sqrt{10}}{7}$ or AWRT 2.3
		3	

	Question 5 Total	10	
--	------------------	----	--

Q	Answer	Marks	Comments
6(a)	$\mathbf{v} = \begin{bmatrix} v \cos 45^\circ \\ v \sin 45^\circ \end{bmatrix}$ $\begin{bmatrix} -I \cos 60^\circ \\ I \sin 60^\circ \end{bmatrix} = \begin{bmatrix} mv \cos 45^\circ \\ mv \sin 45^\circ \end{bmatrix} - \begin{bmatrix} mu \\ 0 \end{bmatrix}$ $\begin{bmatrix} -\frac{1}{2}I \\ \frac{\sqrt{3}}{2}I \end{bmatrix} = m \begin{bmatrix} \frac{\sqrt{2}}{2}v - u \\ \frac{\sqrt{2}}{2}v \end{bmatrix}$ $\frac{\sqrt{3}}{2}I = m \frac{\sqrt{2}}{2}v$ $I = mv \frac{\sqrt{6}}{3}$ $-\frac{1}{2}I = m \left(\frac{\sqrt{2}}{2}v - u \right)$ $mu = mv \frac{\sqrt{2}}{2} + mv \frac{\sqrt{6}}{6}$ $u = v \left(\frac{\sqrt{2}}{2} + \frac{\sqrt{6}}{6} \right) = v \left(\frac{3\sqrt{2} + \sqrt{6}}{6} \right)$ $v = \left(\frac{3\sqrt{2} + \sqrt{6}}{6} \right)^{-1} u = \left(\frac{3\sqrt{2} - \sqrt{6}}{2} \right) u$	<p>M1</p> <p>A1</p> <p>A1</p> <p>M1</p> <p>A1</p>	<p>Uses impulse equation with vectors or components</p> <p>Correct equation(s)</p> <p>Correct impulse in terms of v</p> <p>Uses their impulse to find u in terms of v</p> <p>Correct v Allow any equivalent exact form eg $\left(\frac{2\sqrt{3}}{\sqrt{2} + \sqrt{6}} \right) u$ or $u\sqrt{6 - 3\sqrt{3}}$</p>
		5	

Q	Answer	Marks	Comments
6(a) ALT	$\mathbf{v} = \begin{bmatrix} v \cos 45^\circ \\ v \sin 45^\circ \end{bmatrix}$ $\begin{bmatrix} -I \cos 60^\circ \\ I \sin 60^\circ \end{bmatrix} = m\mathbf{v} - \begin{bmatrix} mu \\ 0 \end{bmatrix}$ $\mathbf{v} = \begin{bmatrix} u - \frac{1}{2m}I \\ \frac{\sqrt{3}}{2m}I \end{bmatrix}$ $\tan 45^\circ = 1$ $mu - \frac{1}{2}I = \frac{\sqrt{3}}{2}I$ $I = (\sqrt{3} - 1)mu$ $\mathbf{v} = \begin{bmatrix} u - \frac{1}{2}(\sqrt{3} - 1)u \\ \frac{\sqrt{3}}{2}(\sqrt{3} - 1)u \end{bmatrix} = \begin{bmatrix} \frac{3 - \sqrt{3}}{2} \\ \frac{3 - \sqrt{3}}{2} \end{bmatrix} u$ $v = \left(\sqrt{2 \left(\frac{3 - \sqrt{3}}{2} \right)^2} \right) u = \left(\frac{3\sqrt{2} - \sqrt{6}}{2} \right) u$	<p>M1</p> <p>A1</p> <p>A1</p> <p>M1</p> <p>A1</p>	<p>Uses impulse equation with vectors or components</p> <p>Correct expression for $\mathbf{v}$</p> <p>Correct impulse</p> <p>Uses their impulse to find $\mathbf{v}$</p> <p>Correct v Allow any equivalent exact form eg $\left(\frac{2\sqrt{3}}{\sqrt{2} + \sqrt{6}} \right) u$ or $u\sqrt{6 - 3\sqrt{3}}$</p>
		5	

Q	Answer	Marks	Comments
7(a)	$\text{Period} = \frac{2\pi}{\sqrt{14}}$ $\frac{7\sqrt{14}}{75} = \frac{4 \times 0.7 \alpha}{\left(2\pi / \sqrt{14}\right)}$ $\alpha = \frac{\pi}{15}$	<p>B1</p> <p>M1</p> <p>A1</p>	<p>Correct period seen or stated</p> <p>ACF eg $2\pi\sqrt{\frac{0.7}{g}}$ or $\frac{\pi\sqrt{14}}{7}$</p> <p>Forms equation using any multiple of arc length over period</p> <p>Correct α</p>
		3	

Q	Answer	Marks	Comments
7(b)	$\frac{\pi}{45} = \frac{\pi}{15} \cos(\sqrt{14}t)$ $\frac{1}{3} = \cos(\sqrt{14}t)$ $t = 0.329 \text{ [seconds to 3dp]}$	<p>M1</p> <p>Allow $\frac{\pi}{45} = \frac{\pi}{15} \sin(\sqrt{14}t)$</p> <p>A1</p> <p>A1</p>	<p>Forms equation to find time with the correct ω</p> <p>Correct equation</p> <p>Correct time</p>
		3	

	Question 7 Total	6	
--	-------------------------	----------	--

[illegible]

Q	Answer	Marks	Comments
9(a)	$28e = 0.2 \times 9.8$	M1	Forms equation to find extension using Hooke's Law
	$e = \frac{0.2 \times 9.8}{28} = 0.070 \text{ [m]}$	A1	Correct extension Allow 0.07
		2	

Q	Answer	Marks	Comments
9(b)	Let x be the displacement below the equilibrium position $T = 28(0.07 + x)$	B1	Correct expression for the tension
	$0.2 \frac{d^2x}{dt^2} = 0.2g - T$ $= 1.96 - 1.96 - 28x$	M1	Forms differential equation
	$\frac{d^2x}{dt^2} = -140x$	A1	Simplifies correct differential equation to SHM form Accept $\frac{d^2x}{dt^2} = -\frac{k}{m}x$
	$\therefore$ SHM as the acceleration is proportional to the displacement and in the opposite direction	E1	Concludes that motion is SHM from correct working
		4	

Q	Answer	Marks	Comments
9(c)	Period = $\frac{2\pi}{\sqrt{140}}$	B1	Correct period Accept 0.169π ACF eg $\frac{\sqrt{35}}{35}\pi$ or $\frac{\pi}{\sqrt{35}}$
		1	

Q	Answer	Marks	Comments
9(d)	$x = 0.03\cos(\sqrt{140}t)$	B1	Correct expression for the displacement Accept $x = 0.03\sin(\sqrt{140}t)$
	For maximum value $T = \frac{\cos^{-1}\left(\frac{0.01}{0.03}\right)}{\sqrt{140}} = 0.1040$	M1	Uses $\frac{\cos^{-1}\left(\frac{0.01}{0.03}\right)}{\sqrt{140}}$
	$b = 0.1040$	A1	Correct value for b
	For minimum value: $T = 2 \times \left(\frac{2\pi}{4\sqrt{140}} - \frac{\cos^{-1}\left(\frac{0.01}{0.03}\right)}{\sqrt{140}} \right) = 0.0574$	M1	Forms an equation to find a
	$a = 0.0574$	A1	Correct equation to find a
	$0.0574 \leq T \leq 0.1040$	A1	Correct inequality
		6	
	Question 9 Total	13	

Q	Answer	Marks	Comments
10	$2\begin{bmatrix} 4 \\ -2 \end{bmatrix} + 3\begin{bmatrix} 2 \\ 1 \end{bmatrix} = 2\begin{bmatrix} 3 \\ 0 \end{bmatrix} + 3\mathbf{v}_B$ $3\mathbf{v}_B = \begin{bmatrix} 8 \\ -1 \end{bmatrix}$ $\mathbf{v}_B = \frac{1}{3}\begin{bmatrix} 8 \\ -1 \end{bmatrix}$ $\mathbf{I}_B = 3\left(\frac{1}{3}\begin{bmatrix} 8 \\ -1 \end{bmatrix} - \begin{bmatrix} 2 \\ 1 \end{bmatrix}\right)$ $\mathbf{I}_B = \begin{bmatrix} 2 \\ -4 \end{bmatrix}$ $\frac{1}{3}\begin{bmatrix} 8 \\ -1 \end{bmatrix} \cdot \begin{bmatrix} 2 \\ -4 \end{bmatrix} = \frac{20}{3}$ $\frac{20}{3} = \sqrt{\frac{65}{9}} \times \sqrt{20} \cos \theta$ $\cos \theta = \frac{20}{\sqrt{20 \times 65}} = \frac{2\sqrt{13}}{13}$ $\theta = 56^\circ$	<p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>A1</p>	<p>Uses conservation of momentum</p> <p>Correct velocity of B after the collision</p> <p>Finds impulse on one sphere</p> <p>Correct impulse</p> <p>Uses scalar product or finds two angles (AWRT 63 and AWRT 7).</p> <p>Correct equation to find angle</p> <p>Correct angle</p>
		7	
	Question 10 Total	7	

Q	Answer	Marks	Comments
11	$0 = 2V\sin\alpha - gt\cos\theta$ $t = \frac{2V\sin\alpha}{g\cos\theta}$ $0 = V\sin\beta - gt\cos\theta$ $t = \frac{V\sin\beta}{g\cos\theta}$ $x_A = 2V\cos\alpha t - \frac{1}{2}gt^2\sin\theta$ $x_B = V\cos\beta t + \frac{1}{2}gt^2\sin\theta$ $d = x_A + x_B$ $= 2V\cos\alpha \times \frac{2V\sin\alpha}{g\cos\theta} + V\cos\beta \times \frac{V\sin\beta}{g\cos\theta}$ $d = 2V^2 \frac{\sin(2\alpha)}{g\cos\theta} + \frac{1}{2}V^2 \frac{\sin(2\beta)}{g\cos\theta}$ $d = \frac{V^2}{2g\cos\theta} (4\sin(2\alpha) + \sin(2\beta))$	M1 A1 A1 M1 M1 M1 A1	Equation for perpendicular velocity of one ball Time in terms of α Time in terms of β PI by $2\sin\alpha = \sin\beta$ from work with perpendicular components. Expressions for distance parallel to the plane Expression for d not in terms of t Uses double angle formula on a two term expression. Correct expression from correct working AG Must be convincingly shown
		7	
	Question 11 Total	7	